

# DUAL POT SAND FILTER

## EQUIPMENT DATA SHEET | Well Service Applications

DESCRIPTION	API 10K	API 15K
<b>MAWP: psig (bar)</b>	10,000 (690)	15,000 (1034)
<b>Design Temp: F (C)</b>	-20° to 350° (-29 to 177)	-20° to 350° (-29 to 177)
<b>Service</b>	H2S (NL)	H2S (NL)
<b>Vessel Design Codes</b>	API 6A, ANSI B31.3, NACE MR0175	API 6A, ANSI B31.3, NACE MR0175
<b>Gas flow rate</b>	0 to 100 MMSCFD	0 to 200 MMSCFD
<b>Liquid flow rate</b>	0 to 7,500 BPD	0 to 15,000 BPD
<b>Screen sizes</b>	100, 150, 200 and 400 microns	100, 150, 200 and 400 microns
<b>Skid</b>	Skid Design to EN12079 / DNV / ABS	Skid Design to EN12079 / DNV / ABS
<b>Gate Valves supplied</b>	Manual FC TYPE	Manual FC TYPE
<b>Skid Dim : mm</b>	3100 x 4060 x 5500	3400 x 4360 x 5800
<b>Skid Wt: kg</b>	26,000	30,000
<b>Delivery</b>	IN STOCK	IN STOCK

