

WELLHEAD DESANDER

EQUIPMENT DATA SHEET | Well Service Applications

| DESCRIPTION | API 5K | API 10K | API 15K |
|-----------------------------|------------------------------------|------------------------------------|------------------------------------|
| MAWP: psig (bar) | 5,000 (344) | 10,000 (690) | 15,000 (1034) |
| Design Temp: F (C) | -20° to 250° (-29 to 121) | -20° to 350° (-29 to 177) | -20° to 350° (-29 to 177) |
| Service | H2S (NL) | H2S (NL) | H2S (NL) |
| Vessel Design Codes | API 6A, ANSI B31.3, NACE MR0175 | API 6A, ANSI B31.3, NACE MR0175 | API 6A, ANSI B31.3, NACE MR0175 |
| Gas flow rate | 0 to 50 MMSCFD | 0 to 100 MMSCFD | 0 to 200 MMSCFD |
| Liquid flow rate | 0 to 5,000 BPD | 0 to 7,500 BPD | 0 to 15,000 BPD |
| Performance | > 10 microns | > 10 microns | > 10 microns |
| Skid | Skid Design to EN12079 / DNV / ABS | Skid Design to EN12079 / DNV / ABS | Skid Design to EN12079 / DNV / ABS |
| Gate Valves supplied | Manual FC TYPE | Manual FC TYPE | Manual FC TYPE |
| Skid Dim : mm | 2000 x 2400 x 5900 | 2400 x 3500 x 6200 | 2500 x 3700 x 6500 |
| Skid Wt: kg | 12,000 | 25,000 | 26,000 |
| Delivery | IN STOCK | IN STOCK | IN STOCK |

