

WELLHEAD DESANDER

EQUIPMENT DATA SHEET | Well Service Applications

DESCRIPTION	API 5K	API 10K	API 15K
MAWP: psig (bar)	5,000 (344)	10,000 (690)	15,000 (1034)
Design Temp: F (C)	-20° to 250° (-29 to 121)	-20° to 350° (-29 to 177)	-20° to 350° (-29 to 177)
Service	H2S (NL)	H2S (NL)	H2S (NL)
Vessel Design Codes	API 6A, ANSI B31.3, NACE MR0175	API 6A, ANSI B31.3, NACE MR0175	API 6A, ANSI B31.3, NACE MR0175
Gas flow rate	0 to 50 MMSCFD	0 to 100 MMSCFD	0 to 200 MMSCFD
Liquid flow rate	0 to 5,000 BPD	0 to 7,500 BPD	0 to 15,000 BPD
Performance	> 10 microns	> 10 microns	> 10 microns
Skid	Skid Design to EN12079 / DNV / ABS	Skid Design to EN12079 / DNV / ABS	Skid Design to EN12079 / DNV / ABS
Gate Valves supplied	Manual FC TYPE	Manual FC TYPE	Manual FC TYPE
Skid Dim : mm	2000 x 2400 x 5900	2400 x 3500 x 6200	2500 x 3700 x 6500
Skid Wt: kg	12,000	25,000	26,000
Delivery	IN STOCK	IN STOCK	IN STOCK

